

Account Information	Component Information	Sample Information
Account Number: 642073-0000-0000 Company Name: PRECISE POWER SYSTEMS Contact: TOM MARKHAM Address: 10520 PLAZA DRIVE WHITMORE LAKE, MI 48189 US Phone Number:	Component ID: 20085T54422 DF Secondary ID: Fuel Type: DIESEL FUEL Manufacturer: Model: Application: UNKNOWN Tank Capacity:	Tracking Number: 20085T54422 Lab Number: I-279665 Lab Location: Indianapolis Data Analyst: CXW Sampled: 2020 Received: 15-May-2020 Completed: 18-May-2020
Filter Information	Miscellaneous Information	
Filter Change: Unknown Filter Type: Information Requested Micron Rating: 9		
Comments	TEST RESULTS are within NORMAL PARAMETERS for this product.	

Test Results									
Test Method	Test Name	Result	Min	Max	Elemental Analysis mod. ASTM D5185	Result	Min	Max	
ASTM D7220	Sulfur (ppm)				Iron (ppm)				
ASTM D2709	Water and Sediment (%)				Chromium (ppm)				
mod. ASTM D6304	Water by Karl Fischer (%)				Nickel (ppm)				
mod. ASTM D6304	Water by Karl Fischer (ppm)	333			Aluminum (ppm)				
Manufacturer	Aerobic Bacteria (Counts)				Copper (ppm)				
Manufacturer	Bacteria (Counts)				Lead (ppm)				
Manufacturer	Fungi (Counts)				Tin (ppm)				
Manufacturer	Mold (Counts)				Cadmium (ppm)				
mod. ASTM D6468	Thermal Stability (%)				Silver (ppm)				
mod. ASTM D445	Viscosity 40°C (cSt)				Vanadium (ppm)				
mod. ASTM D445	Viscosity 100 °C (cSt)				Silicon (ppm)				
mod. ASTM D664	Acid Number (mg KOH/g)				Sodium (ppm)				
ASTM D7689	Cloud Point (°C)				Potassium (ppm)				
ASTM D7346	Pour Point (°C)				Titanium (ppm)				
ASTM D6371	Cold Filter Plug Point (°C)				Molybdenum (ppm)				
ASTM D3828	Closed Cup Flash Point (°C)				Antimony (ppm)				
ASTM D7345	Distillation Initial Boiling Point (°C)				Manganese (ppm)				
"Predicted D86"					Lithium (ppm)				
ASTM D7345	Distillation 10% Recovered (°C)				Boron (ppm)				
"Predicted D86"					Magnesium (ppm)				
ASTM D7345	Distillation 50% Recovered (°C)				Calcium (ppm)				
"Predicted D86"					Barium (ppm)				
ASTM D7345	Distillation 90% Recovered (°C)				Phosphorus (ppm)				
"Predicted D86"					Zinc (ppm)				
ASTM D7345	Distillation Final Boiling Point (°C)								
"Predicted D86"									
ASTM D976	Cetane Index								
ASTM D7777	API Gravity								
ASTM D7777	Density (g/mL)								
Internal Method	Specific Gravity								
ASTM D4868	BTU Per Gallon (BTU/gal)								
ASTM D4868	BTU Per Pound (BTU/lb)								
ASTM D6079	Lubricity (µm)								
ASTM D130	Copper Corrosion								
ASTM D482	Ash Content (mass %)								
ASTM D189	Carbon Residue (%)								
ASTM D7371	% Biodiesel - FAME (%)								
					Particle Count (particles/mL) ISO 4406 & mod. ISO 11500	Result	Min	Max	
					ISO Cleanliness Code	17 / 15 / 12	/ /	/ /	
					> 4µm	1036			
					> 6µm	305			
					> 10µm	67			
					> 14µm	21			
					> 21µm	3			
					> 38µm	0			
					> 70µm	0			
					> 100µm	0			